



O' Tannenbaum – Product Specification



M 1:200

HodgePodge – A variety of study and durable sport and play elements

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities. Climbing trees, a Wasp's nest, Volleyball nets for sporting activities, cable rides for fun and excitement.

At a glance.

Product Family:	HodgePodge	Number of Foundations:	1 pc.
Item Number:	95.200.080	Concrete Volume C20/C25:	1.2 m³
Children's Age:	3+	Number of skilled installers required:	3
Fall Height (DIN EN 1176):	0.50 m (1'-8")	Installation Time without foundation:	6 hours
Length x Width x Height:	2.4 m x 2.4 m x 3.1 m (7'-11" x 7'-11" x 10')	Dimensions of largest part:	Ø 0.1 m x 4.6 m (Ø 0'-1" x 15'-1")
Protective Surfacing Area (DIN EN 1176):	5.4 m x 5.4 m	Weight of heaviest part:	92 kg
Protective Surfacing Area (ASTM 1487):	6.1 m x 6.1 m (19'-9" x 19'-9")	Shipping Volume:	1.7 m³
Minimum space required DIN EN 1176:	22.5 m²	Spare part guarantee:	Lifelong
Minimum space required ASTM 1487:	28.4 m²	Certificate according to EN 1176	No.: Z2.16.01.10256.257 TÜV Product Service

Technical Data.

The following text can also be used for tenders.

Central mast:

Steel post 133 mm (5 1/4"), wall thickness 6.3mm (1/4"), anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process.

Mast node:

Framework-aluminum ball connector; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; with inlying net tensioning system, secured with a durable EPDM-cap.

Rubber membrane:

comprised of durable, vandal-resistant conveyor belt material.

Ropes:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter Ø 16 mm (5/8").

Outer rings:

Bended Framework-steel pipes, Ø 48.3 mm (1 7/8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process.

Netting and suspension ropes:

rope crossing points localized by durable, drop forged aluminium-ballknots (no plastic).


Berliner
 Berliner Seilfabrik GmbH & Co.
 Lengeder Straße 2/4
 D-13407 Berlin

Tel. +49.(0)30.41 47 24-0
 Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com
 www.berliner-seilfabrik.com

