## Instructions for maintenance

In addition to the manufacturer-related service instructions, we strongly advise the operator/owner to consider the corresponding prescriptions of the European Standard EN1176-7.

**K&K Playing** 

## 022712504

One-time maintenance

Check all screw connections; retighten, if necessary.

combination

once. approx. 4-5 weeks after installation

	Recommended regular inspection and maintenance	once a week	twice per month	once a month	four times a year	twice a year	once a year
	Check cleanliness of playing and safety area. Remove any foreign object						
	Check chains for wear, replace if necessary. The nominal chain thickness must not diminish more than 30% (< 5 mm). Beyond that limit, a chain replacement is indispensable.						
$\sum$	Check cleanliness of sliding surfaces, remove protruding parts, exchange damaged sliding course coverings						
	In case of drying cracks, remove splinters of wood and chamfer sharp edges						
$\square$	Where appropriate, check synthetic surfacing material for damages or severe wear, repair or replace, if necessary						
	Check tightness of stand construction: stability of (vertical) posts or supports, retighten screw connections, if necessary.						
	Check further structural components for wear and tightness; retighten, if necessary and replace defective parts.						
	Check bearings and/or joints for tight fixing and easy-running function, replace or grease, if necessary (megaphone).						
$\sum$	Check tension and damages of the climbing rope, replace if necessary						
	Check foundations and structural construction for corrosion or decay, repair or replace if necessary						

Please note: The above-mentioned maintenance intervals only have recommendatory character. They must necessarily be adapted to the local circumstances of each playground (frequency of use, social setting, risk and frequency of vandalism etc.).



