

Instructions for maintenance

Check all screw connections; if necessary srew down

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

Hill slide with 0-41875-701 platform



one-time only approx. 4-5 weeks

again.	after installation					
Recommendations about regular maintenance	1 x weekly	2 x monthly	1 x monthly	4 x yearly	2 x yearly	1 x yearly
Check connection between Robinia post and steel pedestals, screw down bolts if necessary, replace Robinia post if necessary						
Check cleanliness of play- and safety area, take out alien elements						
Check tightness of stand construction (stability of vertical posts or supports), retighten screw connections, if necessary						
Check further structural components for wear and tightness, retighten, if necessary and replace defective parts.						
Check cleanliness of sliding surfaces, remove protruding parts, exchange damaged sliding course covering						
Clean playing sand/playbark						
In case of drying cracks, remove splinters of wood and						

Kaiser & Kühne Freizeitgeräte GmbH

	Check foundations and structural construction for			
	corrosion or decay, repair or replace if necessary.			

Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)