

Published: April 2020

Beetle.01

Urban Design Playpoints are climbers or rockers or twisters. They are Playpoints first and foremost, but they are also very nice pieces of public design, and they are sculptural. All URBAN DESIGN Playpoints are high-end engineered units made from high-quality materials like stainless steel with a brushed finish, powder coated recycled aluminium connectors, high density polyethylene (HDPE)


panels and ITR-bearings for maximum safety and durability.


Beetle.01 impresses with its elegant design and technical superiority. A special rubber bearing element prevents a hard stop and thus ensures a smooth rocking experience. Beetle.01 moves quickly to the right and left!



Beetle.01 Published: April 2020

90.260.614.1	
Product Family	Urban Design
Length x Width x Height (m) Length x Width x Height ('-")	0,6 x 0,9 x 0,5 2-1 x 3-1 x 1-9
Protective Surfacing Area acc. to DIN EN 1176 (m) Protective Surfacing Area acc. to ASTM/CSA (m) Protective Surfacing Area acc. to ASTM/CSA ('-'')	2,6 x 2,9 4,3 x 4,6 14-1 x 15-1
Fall Height acc. to ASTM/CSA('-")	0,51 1-9
○ ○ Age	3
Minimum Space required acc. to DIN EN 1176 (m²) Minimum Space required acc. to ASTM 1487 (ft²)	5,83 163,83
Number of Foundations	2
Concrete Volume C20/C25 (m³)	0,3
Number of skilled Installers required	2
Installation Time without Foundation	1 hour
Dimensions of largest Part (m)	0,6 x 0,9 x 0,5
Weight of heaviest Part (kg)	100
Shipping Volume (m³)	0,63
Total Weight (kg)	120
Spare Part Guarantee	Lifelong





Technical Data

The following text can also be used for tenders.

Tube:

The bent tube with a diameter of Ø 76,1 mm (3") and a wall thickness of 5 mm (%6") is made of stainless steel.

Ball:

The Frameworx® aluminium ball with a diameter of Ø 250 mm (9 13 %s") is sandblasted, powder-coated in colour using a solvent-free epoxy-polyester-process and securely closed with a durable EPDM cap.

Feelers:

The stainless steel feelers are composed of tubes with a diameter of \emptyset 26,9 mm (1 %) and balls welded to them with a diameter of \emptyset 80 mm (3 %).

Bearing:

The axle in the Frameworx® aluminium ball is encapsulated and equipped with a special torsion-elastic spring bearing system.