


Cup Swing – Product Specification



Cup Swing

Discover the comfortable way of swinging with the Cup Swing and the Bowl Swing.



Cup Swing – at a glance.

Product Family:	Playpoints	Number of Foundations:	2 pc.
Item Number:	90.260.531	Concrete Volume C20/C25:	1.2 m³ (43 ft³)
Children's Age:	3+	Number of skilled installers required:	2
Fall Height (DIN EN 1176):	1.7 m (5'-7")	Installation Time without foundation:	3 hours
Length x Width x Height:	3.3 m x 1.3 m x 2.9 m (10'-10" x 4'-4" x 9'-7")	Dimensions of largest part:	2.3 m x 0.4 m x 0.2 m (7'-7" x 1'-4" x 0'-8")
Protective Surfacing Area (DIN EN 1176):	6.8 m x 3.3 m	Weight of the heaviest part:	55 kg (122 lbs)
Protective Surfacing Area (ASTM 1487):	7.0 m x 6.9 m (23'-0" x 22'-8")	Shipping Volume:	2.8 m³ (99 ft³)
Minimum space required DIN EN 1176:	21.5 m²	Shipping Weight:	190 kg (419 lbs)
Minimum space required ASTM 1487:	33.2 m² (358 ft²)	Spare part guarantee:	Lifelong
		Certificate according to DIN EN 1176:	No.: Z2 14 09 10256 223 TÜV Product Service

Technical Data.

The following text can also be used for tenders.

Swing seat:

Nest swing seat made of galvanized steel tube ring, encased with shock absorbing material and wrapped with a shock-absorbing fiber rope, close-knit network of soft steel wire, steel wire strands which are covered with braided polyester yarns. Connection parts: Stainless steel V2A

Nodes:

Framework[®]-aluminum ball connectors; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; securely closed with durable EPDM- caps

Posts:

Steel pipes Ø 133 mm (5 1/4"); wall thickness 5 - 10 mm (3/16" - 3/8") with a round cast aluminum post top; anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

suspension:

U-Rope[®]-round strand ropes with galvanized steel cores, external strands are covered with high abrasion-resistant and UV-resistant polyester-yarn (no Polypropylene); Ø 16 mm, connected to universal joint with steel chains


Berliner
Berliner Seilfabrik GmbH & Co.
Lengeder Straße 2/4
D-13407 Berlin

Tel. +49.(0)30.41 47 24-0
Fax +49.(0)30.41 47 24-33

info@berliner-seilfabrik.com
www.berliner-seilfabrik.com

