

Instructions for maintenance

In addition to the manufacturer-related service instructions, we strongly advise the operator/owner to consider the corresponding prescriptions of the European Standard EN1176-7.



031561701 K&K Sand play yard

Check all screw connections; retighten, if necessary. Cover all

One-time maintenance

screw neads with protective screw caps.			approx. 4-5 weeks after installation					
	Recommended regular inspection and maintenance	once a week	twice per month	once a month	four times a year	twice a year	once a year	
	Clean playing sand							
	Check cleanliness of playing and safety area. Remove any foreign object	jn						
	Check chains of sand pulleys for wear, replace if necessary. The nominal chain thickness must not diminish more than 30% (< 3 mm). Beyond that limit, a chain replacement is indispensable							
	Check rubber parts like seats, hoses, flaps, collars for wear (here chutes of sand pulleys), replace if necessary	e:						
	In case of drying cracks, remove splinters of wood and chamfer sharp edges							
	Where appropriate, check synthetic surfacing material for damages or severe wear, repair or replace, if necessary							
	Check tightness of stand construction: stability of (vertical) posts supports, retighten screw connections, if necessary.	or						
	Check further structural components for wear and tightness; retighten, if necessary and replace defective parts.							
	Check tightness/stability of the connection between stainless stersupport and laminated timber post, replace post, if necessary.	el						
	Check foundations and structural construction for corrosion or decay, repair or replace if necessary							

once,

Please note: The above-mentioned maintenance intervals only have recommendatory character. They must necessarily be adapted to the local circumstances of each playground (frequency of use, social setting, risk and frequency of vandalism etc.).