

## Instructions for maintenance

We recommend, in addition to our instructions for maintenance, to consider carefully the demands of EN 1176-7

## Combi slide (2,40) on tube 0-41166-700 pedestals





Check all screw connections; if necessary screw down again. Cover screw-head with protecting cap.

one-time only approx. 4-5 weeks after installation

	Recommendations about regular maintenance	1 x weekly	2 x monthly	1 x monthly	4 x yearly	2 x yearly	1 x yearly
	Check connection between Robinia post and steel pedestals, screw down bolts if necessary, replace Robinia post if necessary						
	Check cleanliness of play- and safety area, take out alien elements						
	Check stability of vertical posts, tighten bolt-connections if necessary					$\square$	
	Check other component elements for wear and tight connections, tighten connections and replace defective elemens if necessary						
	Check slide chutes for cleanliness, take out protruding elements, repair defect stainless sheet steel			$\square$			
$\square$	In case of dry shakes remove splinters and chamfer edges			$\bigcirc$			
	Check foundation, foundation anchoring and whole construction for corrosion or decay, repair or replace if necessary.						$\square$

Please note: The mentioned maintainance intervals are a recommendation only. They have to be adjusted to the needs and circumstances of a certain playground (e.g.due to the frequency of use, social facilities and vandalism problems etc.)